

Eaton BP/SC-30

Catalog Number: BP/SC-30

Eaton Bussmann series SC rejection box, rejection fuse, time delay, Current limiting, fast acting, Rejection style, 20 A, 480 Vac, 300 Vdc, 100000A (RMS Symmetrical), 10000A (DC) interrupt rating, G class

General specifications

Product Name	Catalog Number
Eaton Bussmann series SC rejection box BP/SC-30	
UPC	Product Length/Depth
051712593137	1.31 in
Product Height	Product Width
0.41 in	0.41 in
Product Weight	Compliances
0.5 lb	Contact factory
	RoHS Compliant



Electrical Ratings

Amperage Rating

30 A

Interrupt rating

100 kAIC Vac

10 kAIC Vdc

Voltage rating

480 Vac, 300 Vdc

General Information

Application

Fusible branch panelboards, HVAC branch circuit protection

Class

Class G

Connection

Ferrule end x ferrule end

Special features

Rejection style

Physical Details

Type

Time delay, current limiting, fast acting

Resources

Catalogs

Bussmann series complete full line catalog no. 1007

BP/SC-30~BP-SC-30~MIDGET FUSE

Specifications and datasheets

Eaton Specification Sheet - BP/SC-30



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia