

1-1/4" NO LEAD BRASS TANK TEES

SPECIFICATIONS:

- Tank tee connects the water line from the pump to the pressure tank plus all the extra tapings needed to complete installation.
- Several lengths available for use with various pressure tanks: 2-1/2", 3", 4", 4-1/2", 14", and 16".
- Several tank connections available: 1" MIP, 1" FIP, 1" quick connect, 1-1/4" MIP, 1-1/4" FIP, 1-1/4" quick connect.
- Other tapings provided: front drain hole (1 or 2) 1/2" FIP for 1" size tees and (1 or 2) 3/4" FIP for 1-1/4" size tees.
- Lateral connections for pipe to and from tank: 1" MIP and 3/4" FIP, or 1-1/4" MIP and 1" FIP.
- All tank tees have two 1/4" FIP tapings on top of the tee, for pressure switch and pressure gauge.
- Tank tees are available as one piece, with O-ring union on tank leg or union as part of the tank connection nut.
- Long version tank tees available as all cast or fabricated with copper tube to give you the length needed.
- 41 different models of No Lead Brass Tank Tees for any model pressure tank or installation needs.



No Lead



C.A. Certified



CERTIFICATIONS:

- IAPMO CA. Certified

MATERIALS LIST

Part Name	Material
Tank Tee Body	No-Lead Brass
O-Ring	NBR (Nitrile)

DIMENSIONS

Part No.	Type	Tank Connection	Lateral	Drain Hole (Qty/Size)	L in.	W in.	H in.	O-Ring Size	Ctn. Qty.	Approx. Wt./Lbs.
BATNL125X	FAB	1-1/4" MIP	1-1/4" MIP & 1" FIP	(1) 3/4"	13.75	5.29	1.72	N/A	10	2.1
BATNL125XC	CAST	1-1/4" MIP	1-1/4" MIP & 1" FIP	(1) 3/4"	14.2	5.61	1.81	N/A	2	3.4
BATNL125XL	FAB	1-1/4" MIP	1-1/4" MIP & 1" FIP	(1) 3/4"	15.8	5.32	1.72	N/A	10	2.3
BATNL125X2	FAB	1-1/4" MIP	1-1/4" MIP & 1" FIP	(2) 3/4"	13.75	5.74	1.72	N/A	10	2.3
BATNL1252XC	CAST	1-1/4" MIP	1-1/4" MIP & 1" FIP	(2) 3/4"	14	5.70	1.72	N/A	2	3.4
BATNL125XL2	FAB	1-1/4" MIP	1-1/4" MIP & 1" FIP	(2) 3/4"	15.7	5.70	1.61	N/A	10	2.5
BATNL125XB	CAST	1-1/4" MIP x Solder	1-1/4" MIP & 1" FIP	(1) 3/4"	3.34	5.31	1.74	N/A	4	1.4
BATNL125X2B	CAST	1-1/4" MIP x Solder	1-1/4" MIP & 1" FIP	(2) 3/4"	3.60	5.74	1.72	N/A	4	1.5
BATNL125CXCS	CAST	1-1/4" MIP x 1" FIP	1" MIP & 3/4" FIP	(2) 1/2"	2.59	5.65	1.47	N/A	4	1.2
BATNL125	CAST	1-1/4" MIP x 1" FIP	1-1/4" MIP & 1" FIP	(1) 3/4"	3.60	5.29	1.72	N/A	4	1.4
BATNL1252	CAST	1-1/4" MIP x 1" FIP	1-1/4" MIP & 1" FIP	(2) 3/4"	4.41	5.78	1.76	N/A	4	1.7
BATNL1252SF	CAST	1-1/4" FIP	1-1/4" MIP & 1" FIP	(2) 3/4"	4.79	5.88	2.02	N/A	4	1.8
*BATNL125QC	CAST	Quick Connect	1-1/4" MIP & 1" FIP	(2) 3/4"	5.04	5.97	1.75	OR220	2	1.7

*Quick Connect end for WELLMATE® Tanks.

MIP = Male Iron Pipe
FIP = Female Iron Pipe



315 Flindt Drive P.O. Box 392
Storm Lake, Iowa 50588-0392 U.S.A.
merrillmfg.com

(800) 831-6962
(712) 732-2760
Fax No. 1-800-ANYFLOW