



## 2 in. Flex Straight Squeeze Connector, Uninsulated

By RACO  
Catalog # 2198

2 in. Flex Straight Squeeze Connector, Uninsulated



### Features

- Rugged metallic construction ensures mechanical protection for the raceway
- Additional sizes available

### Specifications

Certified Listed	<ul style="list-style-type: none"><li>• UL Listed</li><li>• CSA Certified</li></ul>
Buy American Compliant	Contact Manufacturer
EU RoHS Indicator	Contact Manufacturer
Industry Standard(s)	UL 514B
Buy America(n) Qualified	Contact Manufacturer

### Configuration

Connector Type	Squeeze
----------------	---------

### Dimensions

Package Length	8.820 in
Package Width	7.280 in
Package Weight	4.600 lb.
Trade Size	2 in
Package Height	5.470 in

Length	2.109 in
Width	2.191 in
Weight	0.46 lb.
Height	3.05 in
Dimensions	2.109 in x 2.191 in x 3.05 in

### General

Fitting Type	Connectors
Insulation Type	Uninsulated
Conduit Type	Flexible Metal Conduit
Material	Die Cast Zinc
UPC	050169021989

### Logistics

Minimum Pack Quantity	10
Carton Quantity	40
Pallet Quantity	1600

### Product Assets

- [Catalog \[English\]](#)
- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Catalog Page \[English\]](#)