



3/4 in. Service Entrance Liquidtight UF Connector

By RACO
Catalog # [4799-3](#)

3/4 in. Service Entrance Liquidtight UF Connector



Features

- Use a nylon connector when a lightweight corrosion resistant connection is required
- 3 #14, 3 #12, 3#10 UF wire
- Grommet opening: min., 0.20 in. x 0.60 in. - max., 0.26 in. x 0.78 in
- Additional size available

Specifications

Certified Listed	<ul style="list-style-type: none"> • UL Listed • CSA Certified
Buy American Compliant	Contact Manufacturer
EU RoHS Indicator	Contact Manufacturer
Industry Standard(s)	UL 514B
Buy America(n) Qualified	Contact Manufacturer

Dimensions

Trade Size	3/4 in
Length	2.15 in
Grommet Opening Maximum	.26 x .78 in
Grommet Opening Minimum	.20 x .60 in

Width	1.56 in
Weight	0.112 lb.
Height	1.56 in
Dimensions	2.15 in x 1.56 in x 1.56 in

General

Fitting Type	Connectors
Conduit Type	Service Entrance
Accessory Type	Fitting
Material	Nylon
UPC	050169479933

Logistics

Minimum Pack Quantity	15
Carton Quantity	15
Pallet Quantity	4560

Product Assets

- [Catalog \[English\]](#)
- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Catalog Page \[English\]](#)